



INVESTOR IN PEOPLE


The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ


I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed 
Dated 25 July 2003



Patents Act 1977
(Rule 16)


25OCT02 E758401-5 D02882
P01/7700 0.00-0224785.6

The Patent Office

Concept House
Cardiff Road
Newport
South Wales NP10 8QQ

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)



1. Your reference 61014/000

2. Patent application number 0224785.6
(The Patent Office will fill in this part)

3. Full name, address and postcode of the or of each applicant (underline all surnames)
JOHN GUEST INTERNATIONAL LIMITED
Horton Road
West Drayton
Middlesex UB7 8JL

Patents ADP number (if you know it) 04893886001

If the applicant is a corporate body, give the country/state of its incorporation UK

4. Title of the invention TEMPORARY CLOSURE DEVICES AND TUBE COUPLINGS INCORPORATING SUCH DEVICES

5. Name of your agent (if you have one) BOULT WADE TENNANT

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)
VERULAM GARDENS
70 GRAY'S INN ROAD
LONDON WC1X 8BT

Patents ADP number (if you know it) 42001 ✓

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country	Priority application number (if you know it)	Date of filing (day/month/year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application	Date of filing (day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? YES
(Answer 'Yes' if:
a) any applicant named in part 3 is not an inventor, or
b) there is an inventor who is not named as an applicant, or
c) any named applicant is a corporate body.
See note (d))

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description 8

Claim(s) 4

Abstract

Drawing(s) 6

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 9/77) 1

Request for substantive examination (Patents Form 10/77)

Any other documents (Please specify)

11

I/We request the grant of a patent on the basis of this application.

Signature

Date

24 October 2002

12. Name and daytime telephone number of person to contact in the United Kingdom Geoffrey C Bayliss 020 7430 7500

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 01645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

DUPLICATE

TEMPORARY CLOSURE DEVICES AND TUBE COUPLINGS
INCORPORATING SUCH DEVICES

5 This invention relates to temporary closure devices suitable for use in tube couplings and also to tube couplings incorporating temporary closure devices.

10 This invention provides a temporary closure device for a throughway comprising a sleeve to fit in the throughway and a core located in the sleeve, the core having an annular rupturable connection locating the core in the sleeve to prevent flow of fluids through the sleeve, the annular connection being
15 rupturable by displacing the core axially in the sleeve to allow fluid to flow through the sleeve.

20 More specifically, the annular rupturable connection is formed by an annular web extending between the core and the sleeve.

25 Thus, in one arrangement according to the invention the web may be formed integrally with the core and has a rupturable connection with the sleeve.

30 For example, the annular web may be formed integrally with both the core and the sleeve, the connection between the web and the sleeve being rupturable to permit the core to move axially in the sleeve to allow flow through the sleeve.

35 In a further arrangement, the annular web may be bonded to the sleeve, the bond being rupturable to permit the core to move axially in the sleeve to allow flow through the sleeve.

In a still further arrangement, the throughway in

the sleeve may have annular abutment means with which the web engages to locate the core in the sleeve and from which the web can be disengaged by pressing the core into the throughway to allow flow of fluid along the throughway.

In any of the above arrangement the sleeve may be an elongate sleeve having a front portion in which the core is located and a rear portion to which the core may be displaced to allow flow of fluid through the sleeve.

In the latter arrangement the rear portion of the sleeve may be formed with one or more axially extending slots in the wall of the sleeve through which fluid may flow when the core is located in the rear of the sleeve.

More specifically, a plurality of slots may be formed in the rear portion of the sleeve equispaced around the sleeve.

In the case where an elongate sleeve is provided and the core is moulded in the front portion of the sleeve, the core may have an end projecting from the front end of the sleeve with which a tube or other component can act to displace the core into the sleeve to open the passage through the sleeve. The projecting end of the core may taper from the integral annular web to the front of the core. Also, the front of the core may have an integral projecting cruciform shape to receive a tube or other component to displace the core.

In any of the above arrangements the sleeve and core may be moulded plastics components.

The invention also provides a tube coupling body having a throughway open at one end to receive a tube, a locking device in the throughway to engage and secure the tube in the throughway, a seal in the
5 throughway beyond the locking device to engage and seal with the tube when the latter is fully inserted into the throughway and is engaged by the locking device and a closure device located in the throughway beyond the seal to be engaged by the tube as the
10 latter is inserted into the throughway, the closure device incorporating a rupturable seal arranged to be ruptured by full insertion of the tube or pin to permit flow in the throughway.

15 The closure device may comprise a sleeve to be engaged in the throughway, a core located in the sleeve with a rupturable seal extending between the plug and sleeve, the plug being engaged by a tube or pin inserted into the throughway to rupture the seal
20 with the sleeve and displace the plug along the sleeve to allow flow through the sleeve.

In the latter construction the closure device may comprise a sleeve and a core located in the sleeve,
25 the sleeve having a front portion and a rear portion, the plug being located in and supported in the front portion of the sleeve by a thin breakable annular web formed integrally between the core and sleeve to prevent flow of fluids through the sleeve, the core
30 being possibly displaceable into the rear portion of the sleeve and the rear portion of the sleeve having a passage or passages therein to permit flow of fluid passed the core when located in the rear portion.

35 More specifically, the rear portion of the sleeve may be formed with one or more axially extending slots in the wall of the sleeve through which fluid

may flow when the core is located in the rear of the sleeve.

5 In one example according to the invention, a plurality of slots may be formed in the rear portion of the sleeve equispaced around the sleeve for fluid flow when the core is displaced into the rear portion of the sleeve.

10 In accordance with a further feature of the invention the core may be moulded in the front portion of the sleeve and may have an end projecting from the front end of the sleeve on which a tube or other component can act to displace the core into the sleeve
15 to open the passage through the sleeve. Furthermore, the projecting end of the core may taper from the integral annular web to the front of the core and the front of the core may have an integral projecting cruciform shape to receive a tube or other component
20 to displace the core.

The following is a description of some specific embodiments of the invention, reference being made to the accompanying drawings in which:

25 Figure 1 is a partially cross-sectioned view of a tube coupling with an end part of a tube inserted partway into the coupling and a closure device located in the coupling in a closed condition;

30 Figure 2 is a similar view to Figure 1 with the tube end fully inserted into the coupling and the closure device in the open condition;

35 Figure 3 is an enlarged view of part of the coupling, part of the end portion of the tube and the closure device shown in Figure 1;

Figure 4 is an elevation view of the closure device out of the tube coupling;

5 Figure 5 is an perspective view of the closure device; and

Figure 6 is a cut-away perspective view of the closing device.

10 Referring firstly to Figure 1 of the drawings, there is shown a tube coupling indicated generally at 10 and an end portion indicated at 11 of a tube which is inserted partway into the coupling. The tube coupling is generally of the type described and
15 illustrated in my European Patent No. 829671 to which reference should be made for a detailed description of the coupling.

20 The coupling comprises a coupling body indicated generally at 12 comprising a short spigot 13 having a central throughway 14 and external annular ribbing 15 to engage and grip in a soft walled tube (not shown). The spigot of the coupling body leads into an enlarged diameter socket 126 having a bottom wall 17 with which
25 the spigot is integrally formed. The throughway 14 in the spigot opens into an increased diameter bore 18 in the socket at an internal annular step 19 at the bottom of the socket facing outwardly of the socket. The socket has a further stepped increase in bore at
30 20 from which an enlarged diameter end portion extends to terminate in an open end 22 to the coupling body.

35 A collet indicated generally at 23 for locking a tube in the coupling body is mounted in the socket adjacent the open end thereof. The collet comprises an annular skirt 24 having a stepped outer surface formed with reduced diameter portion 25 at a step 26

which engages in the stepped bore 18 with the step 26 abutting the step 20. The skirt 24 has a plurality of resilient arms 27 projecting towards the open end of the socket and is formed with inturned abutment teeth 28 to engage with a tube inserted into the coupling body.

A tube to engage in the coupling body is indicated at 29. The tube has a reduced diameter end portion 30 which projects into the socket of the coupling body through the open end 22, and has an integral encircling annular bead 31 with which the teeth 28 on the collet engage as the tube is inserted into the socket. As shown in Figure 1, the tube is partially inserted into the socket and the bead 31 is in engagement with the outer sides of teeth 28 of the collet.

The bore 18 of the socket 16 contains, further along from the collet 24, a first O-ring seal 32 to engage with the outer surface of the tube inserted into the socket, a spacer 33 and further O-ring seal 34 and finally a closure device indicated generally at 35.

The detailed construction of the closure device is shown in Figures 3 to 6 to which reference will now be made. The closure device comprises a sleeve 37 having a stepped bore the sleeve having a forward portion 38 in which the larger diameter bore is formed containing a slightly small diameter portion bore and a rear portion 39. The sleeve is located between the second O-ring seal 34 in the socket and shoulder 19 where the socket reduces in diameter to the spigot 13. The front portion of sleeve 38 contains a core comprising a central cylindrical portion 40 which is smaller in diameter than the internal diameter of the

sleeve 38 to leave a gap 41 between the core and forward portion of the sleeve. The core is located in the sleeve by means of an annular web 43 of triangular cross-section formed integrally with the core and tapering to a apex formed integrally with the inner surface of the sleeve. The connection between the apex of the web and the inner surface of the sleeve is rupturable to release the core from the sleeve as will be described later.

The core has a frusto-conical portion 42 extending from the web 43 outwardly of the sleeve and to terminate in a projecting cross or cruciform abutment 44 at the forward end of the core. The opposite, rearward end of the core is formed with a similar cruciform projection 35. The core is a close fit in the rear near portion 39 of the sleeve which has a plurality of slots 46 extending into the sleeve from the rearward end to allow flow of fluid around the core.

As indicated earlier, the apex of the web 43 connecting the core 40 to the forward portion 43 of the sleeve is rupturable and the cruciform abutment 44 at the front end of the core is designed to be engaged by the leading end of tube portion 30 as the latter is inserted into the connecting body and the raised bead 31 on the tube comes into engagement with the teeth 28 of the collet. On pressing the tube further into the socket of the coupling body, the end of tube forces the core 35 rearwardly breaking the connection of the core to the sleeve and driving the core into the rear part of the sleeve where fluid flow around the core can take place via the slots 46 in the sleeve. At the same time the raised bead 31 snaps past the tube 28 which then engage on the rearward side of the bead to hold the tube in the socket shown in Figure 2.

sleeve as described earlier. A modification of that arrangement, the core and sleeve may be moulded as separately components with the web being formed integrally with the core and the core can be secured and placed in the front portion of the sleeve by adhering the apex of the web with the sleeve which again provides as rupturable connection. In a further modification, the web on the core projects into a annular slot in the sleeve which holds the web and prevents flow past the core. An excess force to the core will, however, force the core along the sleeve thus disengaging the web from the slot.

In a further modification, the closure device may comprise the core and the front portion of the sleeve, the rear portion being omitted.

The tube coupling may be supplied with a "stuffer pin" formed integrally with the core to position the core in the coupling. The "stuffer pin" can be used to press the core through the sleeve to open the coupling for flow. The stuffer pin is designed to snap off the core in tension to allow it to be removed.

25

30

CLAIMS

1. A temporary closure device for a throughway comprising a sleeve to fit in the throughway and a
5 core located in the sleeve, the core having an annular rupturable connection locating the core in the sleeve to prevent flow of fluids through the sleeve, the annular connection being rupturable by displacing the core axially in the sleeve to allow fluid to flow
10 through the sleeve.

2. A closure device as claimed in claim 1, wherein the annular rupturable connection is formed by an annular web extending between the core and the
15 sleeve.

3. A closure device as claimed in claim 2, wherein the web is formed integrally with the core and has a rupturable connection with the sleeve.
20

4. A closure device as claimed in claim 3, wherein the annular web is formed integrally with both the core and the sleeve, the connection between the web and the sleeve being rupturable to permit the core
25 to move axially in the sleeve to allow flow through the sleeve.

5. A closure device as claimed in claim 3, wherein the annular web is bonded to the sleeve and
30 the bond being rupturable to permit the core to move axially in the sleeve to allow flow through the sleeve.

6. A closure device as claimed in claim 3, wherein the throughway in the sleeve has annular
35 abutment means with which the web engages to locate the core in the sleeve and from which the web can be

disengaged by pressing the core into the throughway to allow flow of fluid along the throughway.

5 7. A closure device as claimed in any of the preceding claims, wherein the sleeve is an elongate sleeve having a front portion in which the core is located and a rear portion to which the core may be displaced to allow flow of fluid through the sleeve.

10 8. A closure device as claimed in claim 7, wherein the rear portion of the sleeve is formed with one or more axially extending slots in the wall of the sleeve through which fluid may flow when the core is located in the rear of the sleeve.

15 9. A closure device as claimed in claim 8, wherein a plurality of slots are formed in the rear portion of the sleeve equispaced around the sleeve.

20 10. A closure device as claimed in any of claims 7 to 9, wherein the core as moulded in the front portion of the sleeve and has an end projecting from the front end of the sleeve with which a tube or other component can act to displace the core into the sleeve
25 to open the passage through the sleeve.

 11. A closure device as claimed in claim 10, wherein the projecting end of the core tapers from the integral annular web to the front of the core.

30 12. A closure device as claimed in claim 10 or claim 11, wherein the front of the core has an integral projecting cruciform shape to receive a tube or other component to displace the core.

35 13. A closure device as claimed in any of the preceding claims, wherein the sleeve and core are

moulded plastics components.

14. A tube coupling comprising a coupling body having a throughway open at one end to receive a tube, a locking device in the throughway to engage and secure the tube in the throughway, a seal in the throughway beyond the locking device to engage and seal with the tube when the latter is fully inserted into the throughway and is engaged by the locking device and a closure device located in the throughway beyond the seal to be engaged by the tube as the latter is inserted into the throughway, the closure device incorporating a rupturable seal arranged to be ruptured by full insertion of the tube or pin to permit flow in the throughway.

15. A tube coupling as claimed in claim 14, wherein the closure device comprises a sleeve to be engaged in the throughway, a core located in the sleeve with a rupturable seal extending between the plug and sleeve, the plug being engaged by a tube or pin inserted into the throughway to rupture the seal with the sleeve and displace the plug along the sleeve to allow flow through the sleeve.

16. A tube coupling as claimed in claim 15, wherein the closure device comprises a sleeve and a core located in the sleeve, the sleeve having a front portion and a rear portion, the plug being located in and supported in the front portion of the sleeve by a thin breakable annular web formed integrally between the core and sleeve to prevent flow of fluids through the sleeve, the core being possibly displaceable into the rear portion of the sleeve and the rear portion of the sleeve having a passage or passages therein to permit flow of fluid passed the core when located in the rear portion.

17. A tube coupling as claimed in claim 16,
wherein the rear portion of the sleeve is formed with
one or more axially extending slots in the wall of the
sleeve through which fluid may flow when the core is
5 located in the rear of the sleeve.

18. A tube coupling as claimed in claim 17,
wherein a plurality of slots are formed in the rear
portion of the sleeve equispaced around the sleeve.
10

19. A tube coupling as claimed in any of claims
16 to 18, wherein the core is moulded in the front
portion of the sleeve and has an end projecting from
the front end of the sleeve on which a tube or other
15 component can act to displace the core into the sleeve
to open the passage through the sleeve.

20. A tube coupling as claimed in claim 19,
wherein the projecting end of the core tapers from the
integral annular web to the front of the core.
20

21. A tube coupling as claimed in claim 20,
wherein the front of the core has an integral
projecting cruciform shape to receive a tube or other
25 component to displace the core.

22. A closure device for a coupling body
substantially as described with reference to and as
illustrated in Figures 3 to 6 of the accompanying
30 drawings.

23. A tube coupling having a closure device
substantially as described with reference to and as
illustrated in Figures 1 and 2 of the accompanying
35 drawings.

FIG. 1.




FIG. 2.




FIG. 3.






FIG. 4






FIG. 5.






FIG. 6.

